

168264325 60376376 001 Seite 1 von 12 Prüfbericht-Nr.: Auftrags-Nr. Test Report No.: Order No.: Page 1 of 12

Kunden-Referenz-Nr.: Auftragsdatum: N/A May 11, 2020

Client Reference No.: Order date:

Auftraggeber: K.Y. Health Medical Equipment Co., Ltd

Client: 777 Wangcongdong Rd, Pidu, Chengdu, Sichuan, 610000, P.R. China

Prüfgegenstand: DISPOSABLE FACE MASK

Test item:

Bezeichnung / Typ-Nr.: Y6002 Identification / Type No.:

Auftrags-Inhalt:

Type test Order content:

EN 14683:2019+AC:2019 except for clause 5.2.6 Prüfgrundlage:

Test specification:

Wareneingangsdatum: May 11, 2020

Date of receipt:

Prüfmuster-Nr.: 20206118

Test sample No.:

Prüfzeitraum: May 11, 2020 to May 22, 2020

Testing period:

Ort der Prüfung: See page 3 Place of testing.

Prüflaboratorium: TÜV Rheinland (Shenzhen)

Testing laboratory. Co., Ltd.

Prüfergebnis*:

Pass Test result*:

geprüft von / tested by:

kontrolliert von / reviewed by:

Angelad

See Attachment: Photo documentation for details.

May 22, 2020 Javen Ke/Assistant Project Engineer

) wen

May 22, 2020 Angela Chen / Department Manager

Unterschrift Datum Name / Stellung Datum Name / Stellung Unterschrift Name / Position Date Signature Date Name / Position Signature

Sonstiges / Other.

The test report consists of EN 14683 test report including this cover page (12 pages) and attachment: Photo documentation (6 pages).

The Biocompatibility (clause 5.2.6) is not evaluated in this test report.

Κe

Zustand des Prüfgegenstandes bei Anlieferung: Prüfmuster vollständig und unbeschädigt Condition of the test item at delivery: Test item complete and undamaged

Legende: 4 = ausreichend 1 = sehr gut 2 = qut3 = befriedigend 5 = mangelhaft P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet 2 = good4 = sufficient Legend: 1 = very good 3 = satisfactory5 = poorP(ass) = passed a.m test specification(s) F(ail) = failed a.m test specification(s) N/A = not applicable N/T = not tested

Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.

This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.



EN 14683:2019+AC: 2019
Medical face masks —
Requirements and test methods

Report Reference No......: 60376376 001

Date of issue....: See cover page
Total number of pages....: See cover page

Testing Laboratory.....: TÜV Rheinland (Shenzhen) Co., Ltd.

Address.....: 1F East & 2-4F, Cybio Technology Building No.1, No.16 Kejibei 2nd

Road, High-Tech Industrial Park North Nanshan District, 518057,

Shenzhen, China

Applicant's name: K.Y. Health Medical Equipment Co., Ltd

China

Test specification:

Standard.....: EN 14683:2019+AC:2019

Test procedure....:: Type test

Non-standard test method.....: N/A

Test Report Form No.....: EN 14683:2019+AC:2019_A

Test Report Form Originator: TÜV Rh (SZ)

Master TRF: 2020-03

Test item description....: DISPOSABLE FACE MASK

Trade Mark....::

K.Y.Health

Manufacturer: Same as the applicant

Model/Type reference....: Y6002 Classification....: Type I



Page 3 of 12

Report No. 60376376 001

| List of Attachments (including a total number of pages in each attachment): | | | | | |
|---|---|--|--|--|--|
| Attachment – Photo Documentation (6 pages) | | | | | |
| Summary of testing: | | | | | |
| Tests performed (name of test and test clause): Construction check according to: Clause 5.1.1 Materials and construction Clause 5.1.2 Design | Testing location: TÜV Rheinland (Shenzhen) Co., Ltd. 1F East & 2-4F, Cybio Technology Building No.1, No.16 Kejibei 2nd Road, High-Tech Industrial Park North Nanshan District, 518057, Shenzhen, China | | | | |
| Clause 5.2.2 Bacterial filtration efficiency (BFE) Clause 5.2.3 Breathability Clause 5.2.4 Splash resistance Clause 5.2.5 Microbial cleanliness (Bioburden) | Sichuan Testing Center of Medical Devices No. 4-28, Xinye Road, High tech west Area, Chengdu, Sichuan, 611731, P.R.China | | | | |

Page 4 of 12

Report No. 60376376 001

Copy of marking plate The artwork below may be only a draft. The use of certification marks on a product must be authorized by the respective NCBs that own these marks. See attachment.

Page 5 of 12 Report No. 60376376 001

| Testing | |
|---|--|
| Date of receipt of test item(s): | See cover page |
| Dates of tests performed: | See cover page |
| Possible test case verdicts: | |
| - test case does not apply to the test object: ! | N/A |
| - test object does meet the requirement: I | P (Pass) |
| - test object was not evaluated for the requirement \dots : $\ensuremath{\mathbf{I}}$ | N/E (collateral standards only) |
| - test object does not meet the requirement: I | F (Fail) |
| | |
| General remarks: | |
| "(See Attachment #)" refers to additional information ap "(See appended table)" refers to a table appended to the The tests results presented in this report relate only to This report shall not be reproduced except in full without ist of test equipment must be kept on file and available Additional test data and/or information provided in the attributed this report a comma/ point is us | he report. the object tested. ut the written approval of the testing laboratory. e for review. attachments to this report. |
| Name and address of factory (ies): | Same as the applicant |
| General product information: | |
| 1, The tested medical mask classified as type I. 2, The Biocompatibility (clause 5.2.6) is not evaluat 3, The test results are for reference only. Relevant intended to be sold in Europe. 4, Evaluation of splash resistance (Clause 5.2.4) was | certification may be needed if the mask is |



| | EN 14683:2019+AC:20 | 19 | | | |
|--------|--|---|---------|--|--|
| Clause | Requirement + Test | Result - Remark | Verdict | | |
| 4 | Classification | | Р | | |
| | Medical face masks specified in this European Standard are classified into two types (Type I and Type II) according to bacterial filtration efficiency whereby Type II is further divided according to whether or not the mask is splash resistant. The 'R' signifies splash resistance. | Type I | Р | | |
| 5 | Requirements | | Р | | |
| 5.1 | General | | | | |
| 5.1.1 | Materials and construction | | Р | | |
| | The medical face mask is a medical device, generally composed of a filter layer that is placed, bonded or moulded between layers of fabric. | 3 ply designed with two layers of non-woven and one layer of meltblown. | Р | | |
| | The medical face mask shall not disintegrate, split or tear during intended use. | | Р | | |
| | In the selection of the filter and layer materials, attention shall be paid to cleanliness. | | Р | | |
| 5.1.2 | Design | | Р | | |
| | The medical face mask shall have a means by which it can be fitted closely over the nose, mouth and chin of the wearer and which ensures that the mask fits closely at the sides. | | P | | |
| | Medical face masks may have different shapes and constructions as well as additional features such as a face shield (to protect the wearer against splashes and droplets) with or without anti-fog function, or a nose bridge (to enhance fit by conforming to the nose contours). | With nose clip | P | | |
| 5.2 | Performance requirements | | Р | | |
| 5.2.1 | General | | Р | | |
| | All tests shall be carried out on finished products or samples cut from finished products. | | Р | | |
| 5.2.2 | Bacterial filtration efficiency (BFE) | | Р | | |
| | When tested in accordance with Annex B, the BFE of the medical face mask shall conform to the minimum value given for the relevant type in Table 1. | See appended table 5.2.2 | Р | | |
| | For thick and rigid masks such as rigid duckbill or cup masks the test method may not be suitable as a proper seal cannot be maintained in the cascade impactor. In these cases, another valid equivalent method shall be used to determine the BFE. | Not such mask. | N/A | | |



| | EN 14683:2019+AC:20 | 19 | |
|--------|--|---|--------|
| Clause | Requirement + Test | Result - Remark | Verdic |
| | When a mask consists of two or more areas with different characteristics or different layer-composition, each panel or area shall be tested individually. | Same characteristics and same layer-composition declared by manufacturer. | N/A |
| | The lowest performing panel or area shall determine the BFE value of the complete mask | See above | N/A |
| 5.2.3 | Breathability | | Р |
| | When tested in accordance with Annex C, the differential pressure of the medical face mask shall conform to the value given for the relevant type in Table 1. | See appended table 5.2.3 | Р |
| | If the use of a respiratory protective device as face mask is required in an operating theatre and/or other medical settings, it might not fulfil the performance requirements with regard to differential pressure as defined in this European Standard. In such case, the device should fulfil the requirement as specified in the relevant Personal Protective Equipment (PPE) standard(s). | | N/A |
| 5.2.4 | Splash resistance | | Р |
| | When tested in accordance with ISO 22609:2004 the | Type I mask. | Р |
| | resistance of the medical face mask to penetration of splashes of liquid shall conform to the minimum value | Evaluation was added per | |
| | given for Type IIR in Table 1. | requirement of manufacturer. See appended table 5.2.4 | |
| 5.2.5 | Microbial cleanliness (Bioburden) | | Р |
| | When tested according to EN ISO 11737-1:2018 the bioburden of the medical mask shall be ≤ 30 CFU/g tested (see Table 1). | See appended table 5.2.5 | Р |
| 5.2.6 | Biocompatibility | | N/E |
| | According to the definition and classification in EN ISO 10993-1:2009, a medical face mask is a surface device with limited contact. | | N/E |
| | The manufacturer shall complete the evaluation of the medical face mask according to EN ISO 10993-1:2009 and determine the applicable toxicology testing regime. | | N/E |
| | The results of testing should be documented according to the applicable parts of the EN ISO 10993 series. | | N/E |
| | The test results shall be available upon request. | | N/E |
| 6 | Marking, labelling and packaging | | Р |
| | Annex I, §13, of the Medical Devices Directive (93/42/EEC) or Annex I, §23, of the Medical Device | See attachment. | Р |
| | Regulation (EU) 2017/745 specifies the information that should be specified on the packaging in which the medical face mask is supplied. | | |



| | EN 14683:2019+AC:2019 | | | | | |
|--------|--|---------|---|--|--|--|
| Clause | Requirement + Test | Verdict | | | | |
| | The following information shall be supplied: | | Р | | | |
| | a) number of this European Standard; | | Р | | | |
| | b) type of mask (as indicated in Table 1). | | Р | | | |
| | EN ISO 15223-1:2016 and EN 1041:2008+A1:2013 should be considered. | | Р | | | |



| EN 14683:2019+AC:2019 | | | | |
|-----------------------|--------------------|-----------------|---------|--|
| Clause | Requirement + Test | Result - Remark | Verdict | |

| 5.2.2 | - | TABLE: Bact | erial filtrati | on efficienc | y (BFE) | | | Р |
|--------------------|--------------------------|--|----------------|----------------------|---|---|---|---------|
| Batch/ lot no.: | Test Specimen no.: | Dimension of the test specimen L x W (mm x mm) | (cm²) | Flow rate (I/min) | Mean of the total plate counts of the two positive controls | Mean plate count of the negative controls | BFE for each test specimen (%) | Remarks |
| 2020611 | 1 | 160×154 | 63.6 | 28.3 | | | 99.43 | |
| 8 | 2 | 159×153 | 63.6 | 28.3 | | | 99.30 | |
| | 3 | 159×153 | 63.6 | 28.3 | 1760 | 0 | 99.13 | |
| | 4 | 160×155 | 63.6 | 28.3 | | | 99.36 | |
| | 5 | 160×154 | 63.6 | 28.3 | | | 99.43 | |

Supplementary information:

^{1,} Each specimen was conditioned at $\underline{21}$ °C and $\underline{85}$ % relative humidity for $\underline{16}$ h to bring them into equilibrium with atmosphere prior to testing.

2, The side of the test specimen was facing towards the challenge aerosol: inside of mask.



| EN 14683:2019+AC:2019 | | | | |
|-----------------------|--------------------|-----------------|---------|--|
| Clause | Requirement + Test | Result - Remark | Verdict | |

| 5.2.3 | | TABLE: Breathability (Different | tial pressure) | | | Р |
|-----------------------|--|---|--|----------------------|-----|-------|
| Batch/ lot no.: | Test Specimen number- Test area number | Differential pressure for each test area (Pa/cm²) | The averaged differential pressure for each test specimen (Pa/cm²) | Flow rate (I/min) | Ren | narks |
| 202061 | 1-1 | 25.0 | | 8.0 | | - |
| 18 | 1-2 | 27.5 | | 8.0 | | _ |
| | 1-3 | 26.8 | 27.5 | 8.0 | | _ |
| | 1-4 | 30.8 | | 8.0 | | |
| | 1-5 | 27.6 | | 8.0 | | - |
| | 2-1 | 24.6 | | 8.0 | | - |
| | 2-2 | 24.7 | 23.5 | 8.0 | | - |
| | 2-3 | 21.0 | | 8.0 | | - |
| | 2-4 | 24.0 | | 8.0 | | - |
| | 2-5 | 23.3 | | 8.0 | | _ |
| | 3-1 | 25.0 | | 8.0 | | - |
| | 3-2 | 20.7 | | 8.0 | | - |
| | 3-3 | 27.1 | 25.3 | 8.0 | | - |
| | 3-4 | 27.6 | | 8.0 | | |
| | 3-5 | 26.0 | | 8.0 | | - |
| | 4-1 | 27.1 | | 8.0 | | - |
| | 4-2 | 26.7 | | 8.0 | | - |
| | 4-3 | 25.6 | 27.7 | 8.0 | | |
| | 4-4 | 28.6 | | 8.0 | | - |
| | 4-5 | 30.6 | | 8.0 | | - |
| | 5-1 | 29.7 | | 8.0 | | - |
| | 5-2 | 25.4 | | 8.0 | | |
| | 5-3 | 24.2 | 26.4 | 8.0 | | - |
| | 5-4 | 26.5 | | 8.0 | | _ |
| | 5-5 | 26.1 | | 8.0 | | - |

Supplementary information:

Each specimen was conditioned at $\underline{21}$ °C and $\underline{85}$ % relative humidity for $\underline{4}$ h to bring them into equilibrium with



| EN 14683:2019+AC:2019 | | | | |
|-----------------------|--------------------|-----------------|---------|--|
| Clause | Requirement + Test | Result - Remark | Verdict | |

atmosphere prior to testing.

| 5.2.4 | TABLE: Sp | olash resistance | | | P |
|-----------|-----------|------------------|-----------------------------|----------------------------|---------|
| Batch/ Io | t no.: | Test mask no.: | The material of tested mask | Test result (Pass/fail) | Remarks |
| 20206118 | | 1 | | Pass | |
| | | 2 | 1 [| Pass | |
| | | 3 | 1 [| Pass | |
| | | 4 | 1 [| Pass | |
| | | 5 | 1 [| Pass | |
| | 6 7 | 1 Γ | Pass | | |
| | | 1 [| Pass | | |
| | | 8 | 1 Γ | Pass | |
| | | 9 | 1 Γ | Pass | |
| | | 10 | 1 [| Pass | |
| | | 11 | 1 [| Pass | |
| | 12 | 1 [| Pass | | |
| | 13 | 1 [| Pass | | |
| | | 14 | See clause | Pass | |
| | | 15 | 5.1.1 for detail | Pass | |
| | | 16 | 1 [| Pass | |
| | | 17 | 1 [| Pass | |
| | | 18 | 1 [| Pass | |
| | | 19 | 1 | Pass | |
| | | 20 | 1 | Pass | |
| | | 21 | 1 | Pass | |
| | | 22 | 1 | Pass | |
| | | 23 | 1 | Pass | |
| | | 24 | 1 | Pass | |
| | | 25 | 1 | Pass | |
| | | 26 | 1 | Pass | |
| | | 27 | 1 | Pass | |
| | | 28 | 1 | Pass | |



| | EN 14683:2019+AC:2019 | | | | | | |
|--------|---|--|--|------|---|--|--|
| Clause | ause Requirement + Test Result - Remark Verdict | | | | | | |
| | 29 | | | Pass | | | |
| | 30 | | | Pass | - | | |
| | 31 | | | Pass | - | | |
| | 32 | | | Pass | - | | |

Supplementary information:

- 1, Each specimen was conditioned at $\underline{21}$ °C and $\underline{85}$ % relative humidity for $\underline{4}$ h to bring them into equilibrium with atmosphere prior to testing.
- 2, The description of target area tested: the centre of the specimen.
- 3, Any technique used to enhance visual detection of synthetic blood: cotton absorbent swab.
- 4, The temperature and relative humidity for testing: 21 °C and 80 %.
- 5, Description of any pre-treatment techniques used: N/A.

| 5.2.5 | TABLE: M | TABLE: Microbial cleanliness (Bioburden) | | | | |
|-----------------|----------|--|-------------------------------|--|---------|---|
| Batch/ lot no.: | | Mask(under test) no.: | Weight of each mask (g) | Total bioburden per individual mask (CFU/g) | Remarks | |
| 20206118 | | 1 | 3.1 | 16 | | |
| | | 2 | 3.0 | 6 | | |
| | | 3 | 2.9 | 6 | | |
| | | 4 | 2.9 | 10 | | |
| | | 5 | 3.0 | 7 | - | - |

End of EN 14683 test report

Photo Documentation

TÜVRheinland®

Report No.: 60376376 001

Page 1 of 6

Product: DISPOSABLE FACE MASK




Figure 1 View of packaging box for mask (Final marking of package box refer to Figure 7 to Figure 10 below)



Figure 2 View of packaging for mask in box

Photo Documentation

TÜVRheinland®

Report No.: 60376376 001

Page 2 of 6

Product: **DISPOSABLE FACE MASK**




Figure 3 View of mask



Figure 4 View of mask

Photo Documentation

TÜVRheinland®

Report No.: 60376376 001

Page 3 of 6

Product: DISPOSABLE FACE MASK



Figure 5 Inner view of mask - layers




Figure 6 Inner view of mask - nose clip

Photo Documentation

TÜVRheinland®

Report No.: 60376376 001

Page 4 of 6

Product:

DISPOSABLE FACE MASK



Figure 7 Front/ rear view of Package on box for mask



Figure 8 Top view of Package on box for mask

Photo Documentation

TÜVRheinland®

Report No.: 60376376 001

Page 5 of 6

Product: DISPOSABLE FACE MASK



Figure 9 Side view of Package on box for mask




Figure 10 Side view of Package on box for mask

Photo Documentation



Report No.: 60376376 001

Page 6 of 6

Product: DISPOSABLE FACE MASK

Type Designation: Y6002

| QUALIFIED CERTIFICATE | | | | | | |
|--|-------------------------------------|--|--|--|--|--|
| | | | | | | |
| PRODUCT NAME 产品名称 | DISPOSABLE FACE MASK | | | | | |
| EXECUTION STANDARD 执行标准 | EN14683-2019 | | | | | |
| 主要成分 | 65%无纺布,35%熔喷布 | | | | | |
| Main Component | Non-woven Fabric, melt-blown fabric | | | | | |
| PRODUCT MODEL 产品型号规格 | Y6002 17.5cm*9.5cm | | | | | |
| LOT NO. 批次号 | 20206118 | | | | | |
| MANUFACTURE DATE 生产日期 | 2020.04.20 | | | | | |
| PRODUCT QTY 产品数量 | 50 pcs | | | | | |
| PERIOD OF VALIDITY 有效期 | 2 YEARS 2年 | | | | | |
| 制造商:四川康源化医疗器械有限公司 | | | | | | |
| K.Y.HEALTH MEDICAL EQUIPMENT CO., LTD. | | | | | | |
| 生产地址:四川省成都市郫都区望从东路777号 | | | | | | |
| 777 WANGCONGDONG RD, PIDU DISTRICT, CHENGDU, SICHUAN | | | | | | |

Figure 11 Qualified certificate in Package for mask

END OF THE PHOTO DOCUMENTATION