

Key **Features**

- 2nd generation laser phosphor technology with up to 30,000 hours lifespan
- 4,200 ANSI Lumens offering bright images in any environment
- Up to 300" ultra large screen that is easily installed and set up
- 0.49 short throw for immersive edge blending without any shadows
- Installation flexibility:
 H/V keystone, 4 corner adjustment, 360°
 projection and portrait mode



Product **Description**

The Luminous Superior series is ViewSonic's lamp-free high brightness projector for both business and education. The LS710HD adopts industry-leading 2nd generation laser phosphor technology, delivers 4,200 ANSI Lumens while eliminating the use of toxic mercury, reducing the cost and effort of frequent lamp replacement and lowering total cost of ownership. The lamp-free light source offers enhanced sustainability for a greener environment while delivering clear and bright images with vivid colors and 1080p resolution. Boasting short throw ratio, flexible installation and easy image adjustments, the projector enables effortless edge blending to create an immersive experience for any space, be it a restaurant, gym, gallery, etc. With 0.49 short throw ratio, the projector can provide 100" large screen size from only 1.1 m away without being bothered by the shadows.

The LS710HD allows perfectly-shaped images even from an angled projection with H/V keystone and 4 corner correction and offers versatile application with 360° projection and portrait mode. The projector also comes with HDMI 2.0b, ensuring you access to original 4K quality content with HDR/HLG support.





- 1. Front IR 2. Lens 3. HDMI 1.4/ HDCP 1.4 4. HDMI 2.0/ HDCP 2.2 5. USB-A (5V/1.5A, Service) 6. Audio Out 7. RJ45 (LAN Control)

- 8. RS232 9. Focus Ring 10. LED Indicator 11. Power Button 12. Keypad & IR

Visit Us

www.viewsonic.com

SPECIFICATION				
Native Resolution:	1920x1080			
Brightness:	4200 (ANSI Lumens)	Р		
Contrast Ratio:	3000000:1	Р		
Display Color:	1.07 Billion Colors			
Light Source Type:	Laser Phosphor	0		
Light Source Life (hours) with Normal Mode:	20000	C N		
Light Source Life (hours) with SuperEco Mode:	30000 (Eco)	G		
Lens:	F=2.8, f=7.51mm	A		
Projection Offset:	132%+/-5%	Р		
Throw Ratio:	0.49			
Optical Zoom:	Fixed			
Digital Zoom:	0.8x-2.0x			
Image Size:	40"-300"			
Throw Distance:	0.43-3.25m (100"@1.08m)	0		
Keystone:	H:+/-15° , V:+/-15°			
Audible Noise (Normal):	32dB			
Audible Noise (Eco):	29dB			
Input Lag:	49.9ms			
Resolution Support:	VGA(640 x 480) to 4K UHD(3840 x 2160)			
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 4K UHD	U		
Horizontal Frequency:	15K-102KHz			
Vertical Scan Rate:	23-120Hz			
INPUT				
HDMI:	2 (HDMI 2.0/ HDCP 2.2 HDMI 1.4/ HDCP 1.4)	ST P		
OUTPUT		R		
Audio-out (3.5mm):	1	Q		
Speaker:	15W x2	W		
USB Type A (Power):	1 (5V/1.5A)	OI		
CONTROL		W		
RS232 (DB 9-pin male):	1			
RJ45 (LAN control):	1			
USB Type A (Services):	1 (share with USB A Output)			

OTHERS

OTHERS			
	Power Supply Voltage:	100-240V+/- 10%, 50/60Hz (AC in)	
	Power Consumption:	Normal: 245W Standby: <0.5W	
	Operating Temperature:	0~40°C	
	Carton:	Brown	
	Net Weight:	4.5kg	
	Gross Weight:	6.6kg	
	Dimensions (WxDxH) with Adjustment Foot:	337x265x131.5mm	
	Packing Dimensions:	496x195x387mm	
	OSD Language:	English, French, German, Spanish, Italian, Portuguese, Dutch, Swedish, Finnish, Greek, Norwegian/Danish, Polish, Russian, Simplified_Chinese, Traditional_Chinese, Korean, Arabic, Japanese, Thai, Hungarian, Czechoslovak, Turkish, Farsi. Vietnamese, Indonesian, Romanian, Slovakian, total 27 languages	
	User Guide Language:	English, S-Chinese, T-Chinese, Indonesian, Finish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, total 20 languages	
STANDARD ACCESSORY			
	Power Cord:	1	
	Remote Control:	1	
	QSG:	Yes	
	Warranty Card:	Yes (CN Only)	
OPTIONAL ACCESSORY			
	Wall/Ceiling Mount:	PJ-WMK-007	