Technical specifications

Cambridge Audio

SX50 speaker



- Highly optimised woofer magnet systems to deliver deep bass and high efficiency
- Silk dome tweeter to combine smooth sound with high levels of detail and efficiency
- Dedicated foam damper behind tweeter diaphragm reduces reflections and deepens stage depth
- Treated paper cone to provide a smooth and even frequency response
- Precisely optimized crossovers for the most neutral, smooth and phase linear response
- Rigid MDF cabinet modelled using CAD so that the speaker dimensions minimise standing waves

Detailed Specifications

Sensitivity	87dB
Frequency response	50Hz – 22kHz
Impedance	8 Ohms
Recommended amplifier power	10-100 Watts
Drivers	Tweeter: 1 x 25mm (1") silk dome tweeter Mid/Bass: 1 x 135mm (5.25") treated paper cone
Crossover	2 way
Ported	1 rear
Colour	Black or Walnut
Dimensions (H x W x D)	225 x 161 x 240mm, (8.9 x 6.3 x 9.4")
Weight	3.0kg (6.6lbs)

© Cambridge Audio 2010 Cambridge Audio is a brand of Audio Partnership Plc, Registered Office: Gallery Court, Hankey Place, London SE1 4BB, United Kingdom. Registered in England No. 2953313

www.cambridge-audio.com

Cambridge Audio's policy is one of continuous improvement. Design and specifications are therefore subject to change without prior notice