

## **ZU720T**

World's first fixed lens 7500 lumen WUXGA laser projector









- 7500 lumen fixed lens Ultra bright for installations where high brightness is required
- Full lens shift Motorised lens shift for simple set up
- Large zoom range 1.8x zoom expands placement opportunities
- 30,000 hours laser light source Little to no maintenance for up to 30,000 hours

The ZU720T is the world's first fixed lens 7500 lumen WUXGA laser projector. Delivering high brightness along with 4K and HDR compatibility, the ZU720T offers low maintenance and extremely long-life DuraCore laser projection technology.

This high-spec projector features a large 1.8x zoom and 1.4~2.5:1 throw ratio, full lens shift and built-in dual 10W speakers for unrivalled flexibility.

Suitable for a wide variety of applications, the ZU720T is perfect for large venues, classrooms, lecture theatres, museums and houses of worship.

The added flexibility of HDBaseT and LAN make this projector an affordable fit and forget solution.

## **Specifications**

mm

(simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese  24/7 operation Yes  360° operation Yes  Operating conditions 10% to 85% Humidity, non-condensing  Remote control Backlit ProAV remote  Heat dissipation 2.013BTU/hour  Speaker count 2  Watts per speaker 10W  Networking  LAN Yes  Power  Power consumption (standby)  Power consumption (min) 370W  Power consumption (max) 590W  Weight and dimensions  Net weight 12.7kg  Dimensions (W x D x H) 484 x 178.5 x 376		
Resolution   WUKGA (1920x1200)   Brightness   7.500 lumens		
Brightness		DLP
Contrast ratio - full on/off         2.000:1           Native aspect ratio         2.000:1           Aspect ratio - compatible         4:3,16:9           Keystone correction - horizontal         +/-30°           Keystone correction - vertical         +/-30°           Screen size         1.02m − 7.62m (40° − 300°) diagonal           Lamp info         Light source type           Lage Ilife         30.000 hours           Optical         Throw ratio           Throw ratio         1.4:1 − 2.5:1           Projection distance (m)         1.2m − 16.5m           Zoom         1.8           Zoom type         Manual           Focal length (mm)         20.68−37.23           Lens shift         Vertical: +/-55%, Horizontal: +/-25%           Lens shift         Yes - {(downloads_link)}           Connectivity         Inputs 1 × HDMI 1.4a 3D support, 1 × HDMI 2.0, 1 × VGA, 1 × Audio 3.5mm, 1 × HDBaseT, 1 × 3D sync           Outputs 1 × HDMI 1.4a 3D support, 1 × Audio 3.5mm, 1 × 3D sync, 2 × USB-A power 1.5A           Control 1 × 12V trigger, 1 × USB-B service, 1 × RJ45, 1 × Wired remote, 1 × RS232           General           Noise level (typical)         27dB           Noise level (typical)         27dB           Noise level (max)         31dB	Resolution	WUXGA (1920x1200)
Contrast ratio - full on/off   2,000:1   Native aspect ratio	Brightness	7.500 lumens
Native aspect ratio - compatible	Contrast ratio - dynamic	1.000.000:1
Aspect ratio - compatible         4:3,16:9           Keystone correction - horizontal         +/-30°           Keystone correction - vertical         4/-30°           Screen size         1.02m - 7.62m (40° ~ 300°) diagonal           Lamp info         Light source type           Last Biffe         30.000 hours           Optical         Throw ratio           Projection distance (m)         1.2m - 16.5m           Zoom         1.8           Zoom type         Manual           Focal length (mm)         20.68-37.23           Lens shift         Vertical: +/-55%, Horizontal: +/-25%           Lens shift         Vertical: +/-55%, Horizontal: +/-25%           Connections         Inputs 1 x HDMI 1.4a 3D support, 1 x HDMI 2.0, 1 x VGA, 1 x Audio 3.5mm, 1 x HDMI 1.4a 3D support, 1 x Audio 3.5mm, 1 x 3D sync           Outputs 1 x HDMI 1.4a 3D support, 1 x Audio 3.5mm, 1 x 3D sync         Outputs 1 x HDMI 1.4a 3D support, 1 x Audio 3.5mm, 1 x 3D sync           Control 1 x 12V trigger, 1 x USB-B service, 1 x RJ45, 1 x wired remote, 1 x RJ45, 2 x B and RJ45, 2	Contrast ratio - full on/off	2.000:1
Keystone correction	Native aspect ratio	16:10
Notice   N	Aspect ratio - compatible	4:3,16:9
Keystone correction - vertical   1.02m - 7.62m (40" ~ 300") diagonal	Keystone correction -	+/-30°
Screen size         1.02m – 7.62m (40* ~ 300") diagonal           Lamp info         Light source type         DuraCore Laser           LASER life         30.000 hours           Optical         1.4:1 ~ 2.5:1           Throw ratio         1.4:1 ~ 2.5:1           Projection distance (m)         1.2m ~ 16.5m           Zoom         1.8           Zoom type         Manual           Focal length (mm)         20.68~37.23           Lens shift         Vertical: +/-55%, Horizontal: +/-25%           Lens shift         Yes - {{downloads_link}}           Connectivity         Inputs 1 x HDMI 1.4a 3D support, 1 x HDMI 2.0, 1 x VGA, 1 x Audio 3.5mm, 1 x HDBaseT, 1 x 3D sync           Outputs 1 x HDMI 1.4a 3D support, 1 x Audio 3.5mm, 1 x 3D sync, 2 x USB-A power 1.5A         Control 1 x 12V trigger, 1 x VBS-B service, 1 x RJ45, 1 x Wired remote, 1 x RS232           General         Noise level (typical)         27dB           Noise level (typical)         27dB           Noise level (typical)         27dB           Noise level (typical)         27dB           Security         Security bar, Kensington Lock, Password protected interface in PSx           IP rating         IPSx           OSD / display languages         23 languages: Arabic, Czech, Danish, Dutch, English, Farsi, French, German, Greek, Indonesian, Italian, Japanese, Fr	horizontal	
Screen size		+/-30°
Lamp info Light source type LASER life 30.000 hours  Optical Throw ratio 1.4:1 ~ 2.5:1 Projection distance (m) 1.2m − 16.5m Zoom 1.8 Zoom type Manual Focal length (mm) 20.68 − 37.23 Lens shift Vertical: +/-55%, Horizontal: +/-25% Lens shift Yes - {{downloads_link}}  Connectivity Connections  Inputs 1 x HDMI 1.4a 3D support, 1 x HDMI 2.0, 1 x VGA, 1 x Audio 3.5mm, 1 x HDBaseT, 1 x 3D sync Outputs 1 x HDMI 1.4a 3D support, 1 x Audio 3.5mm, 1 x 3D sync, 2 x USB-A power 1.5A Control 1 x 12 V trigger, 1 x USB-B service, 1 x RJ45, 1 x Wired remote, 1 x RS232  General Noise level (typical) Noise level (max) Security Security Security bar, Kensington Lock, Password protected interface IP rating IP Fating OSD / display languages 23 languages: Arabic, Czech, Danish, Dutch, English, Farsi, French, German, Greek, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese  24/7 operation Yes Operating conditions Remote control Heat dissipation 20 Sackit ProaV remote Heat dissipation 20 Spaner Speaker count 20 Watts per speaker 10W Networking LAN Yes Power Power consumption (min) 370W Power consumption (min) 590W Weight and dimensions Net weight 12.7kg Dimensions (W x D x H) 484 x 178.5 x 376		
Light source type  LASER life  30.000 hours  Optical  Throw ratio  1.4:1 ~ 2.5:1  Projection distance (m)  1.8  Zoom  1.8  Zoom ype  Manual  Focal length (mm)  Lens shift  Vertical: +/-55%, Horizontal: +/-25%  Lens shift  Connectivity  Connections  Inputs 1 x HDM1 1.4a 3D support, 1 x HDM1 2.0, 1 x VGA, 1 x Audio 3.5mm, 1 x HDM1 1.4a 3D support, 1 x Audio 3.5mm, 1 x BD support, 1 x BD support, 1 x Audio 3.5mm, 1 x BD support, 1 x BD support, 1 x Audio 3.5mm, 1 x BD support, 1 x BD		1.02m ~ 7.62m (40" ~ 300") diagonal
Description   Control	•	
Optical         1.4:1 ~ 2.5:1           Projection distance (m)         1.2m ~ 16.5m           Zoom         1.8           Zoom type         Manual           Focal length (mm)         20.68~37.23           Lens shift         Vertical: +/-55%, Horizontal: +/-25%           Lens shift         Vertical: +/-55%, Horizontal: +/-25%           Lens shift         Vertical: +/-55%, Horizontal: +/-25%           Cens shift         Vertical: +/-55%, Horizontal: +/-25%           Connectivity         Inputs 1 x HDMI 1.4a 3D support, 1 x HDMI 2.0, 1 x VGA, 1 x Audio 3.5mm, 1 x 4DBaseT, 1 x 3D sync           Outputs 1 x HDMI 1.4a 3D support, 1 x Audio 3.5mm, 1 x 3D sync, 2 x USB-A power 1.5A         Control 1 x 12V trigger, 1 x USB-B service, 1 x RJ45, 1 x Wired remote, 1 x RS232           General         Noise level (typical)         27dB           Noise level (max)         31dB           Security         Security bar, Kensington Lock, Password protected interface IPs           IP rating         IP5x           OSD / display languages         23 languages: Arabic, Czech, Danish, Dutch, English, Farsi, French, German, Greek, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romainan, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese           24/7 operation         Yes           360° operation         Yes           Operating c		
Throw ratio         1.4:1 ~ 2.5:1           Projection distance (m)         1.2m ~ 16.5m           Zoom         1.8           Zoom type         Manual           Focal length (mm)         20.68~37.23           Lens shift         Vertical: +/-55%, Horizontal: +/-25%           Lens shift         Yes - {{downloads_link}}           Connectivity         Inputs 1 x HDMI 1.4a 3D support, 1 x HDMI 2.0, 1 x VGA, 1 x Audio 3.5mm, 1 x HDMI 1.4a 3D support, 1 x Audio 3.5mm, 1 x 3D sync, 2 x USB-A power 1.5A           Control 1 x 12V trigger, 1 x USB-B service, 1 x RJ45, 1 x Wired remote, 1 x RS232           General           Noise level (typical)         27dB           Noise level (max)         31dB           Security         Security bar, Kensington Lock, Password protected interface IP Pating           OSD / display languages         23 languages: Arabic, Czech, Danish, Dutch, English, Farsi, French, German, Greek, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romainan, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese           24/7 operation         Yes           360° operation         Yes           Operating conditions         10% to 85% Humidity, non-condensing           Remote control         Backlit ProAV remote           Leat dissipation         2,013BTU/hour           Speaker count		30.000 hours
Projection distance (m)	•	
Zoom type		
Zoom type		
Pocal length (mm)		
Lens shift         Vertical: +/-55%, Horizontal: +/-25%           Lens shift         Yes - {{downloads_link}}           Connectivity         Inputs 1 x HDMI 1.4a 3D support, 1 x HDMI 2.0, 1 x VGA, 1 x Audio 3.5mm, 1 x HDMI 1.4a 3D support, 1 x Audio 3.5mm, 1 x 3D sync, 2 x USB-A power 1.5A           Control 1 x 12V trigger, 1 x USB-B service, 1 x RJ45, 1 x Wired remote, 1 x RS232           General         27dB           Noise level (typical)         27dB           Noise level (max)         31dB           Security         Security bar, Kensington Lock, Password protected interface IPF x           IP rating         IP5x           OSD / display languages         23 languages: Arabic, Czech, Danish, Dutch, English, Farsi, French, German, Greek, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese           24/7 operation         Yes           Operating conditions         10% to 85% Humidity, non-condensing           Remote control         Backlit ProAV remote           Heat dissipation         2.013BTU/hour           Speaker count         2           Watts per speaker         10W           Networking         LAN           LAN         Yes           Power consumption (min)         370W           Power consumption (min)         370W </th <th></th> <th></th>		
Lens shift  Yes - {{downloads_link}}  Connectivity  Connections  Inputs 1 x HDMI 1.4a 3D support, 1 x HDMI 2.0, 1 x VGA, 1 x Audio 3.5mm, 1 x HDBaseT, 1 x 3D sync  Outputs 1 x HDMI 1.4a 3D support, 1 x Audio 3.5mm, 1 x 3D sync, 2 x USB-A power 1.5A  Control 1 x 12V trigger, 1 x USB-B service, 1 x RJ45, 1 x Wired remote, 1 x RS232  General  Noise level (typical)  Noise level (max)  Security  Security bar, Kensington Lock, Password protected interface IP rating  IP5x  OSD / display languages  23 languages: Arabic, Ozech, Danish, Dutch, English, Farsi, French, German, Greek, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese  24/7 operation  Yes  Operating conditions  Remote control  Backlit ProAV remote  Heat dissipation  Speaker count  2  Watts per speaker  10W  Networking  LAN  Yes  Power  Power consumption  (standby)  Power consumption (min)  Power consumption (max)  Weight and dimensions  Net weight  12.7kg  Dimensions (W x D x H)  484 x 178.5 x 376		
Connectivity Connections  Inputs 1 x HDMI 1.4a 3D support, 1 x HDMI 2.0, 1 x VGA, 1 x Audio 3.5mm, 1 x HDBaseT, 1 x 3D sync Outputs 1 x HDMI 1.4a 3D support, 1 x Audio 3.5mm, 1 x 3D sync, 2 x USB-A power 1.5A Control 1 x 12V trigger, 1 x USB-B service, 1 x RJ45, 1 x Wired remote, 1 x RS232  General Noise level (typical) Noise level (max) 31dB Security Security bar, Kensington Lock, Password protected interface IP rating IP5x OSD / display languages 23 languages: Arabic, Czech, Danish, Dutch, English, Farsi, French, German, Greek, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese  24/7 operation Yes 360° operation Yes Operating conditions Remote control Backlit ProAV remote Heat dissipation 2.013BTU/hour Speaker count 2 Watts per speaker 10W Networking LAN Yes Power Power consumption (min) 370W Power consumption (max) Spe0W Weight and dimensions Net weight 12.7kg Dimensions (W x D x H) 484 x 178.5 x 376	Lens shift	Vertical: +/-55%, Horizontal: +/-25%
Inputs 1 x HDMI 1.4a 3D support, 1 x HDMI 2.0, 1 x VGA, 1 x Audio 3.5mm, 1 x HDBaseT, 1 x 3D sync   Outputs 1 x HDMI 1.4a 3D support, 1 x Audio 3.5mm, 1 x 3D sync, 2 x USB-A power 1.5A   Control 1 x 12V trigger, 1 x USB-B service, 1 x RJ45, 1 x Wired remote, 1 x RS232	Lens shift	Yes - {{downloads_link}}
1 x Audio 3.5mm, 1 x HDBaseT, 1 x 3D sync	Connectivity	
General Noise level (typical) Noise level (typical) Security Security bar, Kensington Lock, Password protected interface IP rating OSD / display languages IP5x OSD / display languages Security languages Security languages Security languages Security bar, Kensington Lock, Password protected interface IP5x Security languages: Arabic, Czech, Danish, Dutch, English, Farsi, French, German, Greek, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese  24/7 operation Yes Operating conditions 10% to 85% Humidity, non-condensing Remote control Backlit ProAV remote Heat dissipation 2.013BTU/hour Speaker count 2 Watts per speaker 10W Networking LAN Yes Power Power consumption (standby) Power consumption (min) 970W Power consumption (min) 970W Power consumption (max) 590W Weight and dimensions Net weight 12.7kg Dimensions (W x D x H) 484 x 178.5 x 376	Connections	1 x Audio 3.5mm, 1 x HDBaseT, 1 x 3D sync  Outputs 1 x HDMI 1.4a 3D support, 1 x Audio 3.5mm, 1 x 3D sync, 2 x USB-A power 1.5A  Control 1 x 12V trigger, 1 x USB-B service, 1 x RJ45, 1 x
Noise level (typical)  Noise level (max)  Security Security bar, Kensington Lock, Password protected interface IP rating  OSD / display languages  Remote control Heat dissipation Speaker count Watts per speaker LAN  Networking LAN  Power Power consumption (min) Power consumption (min) Power consumption (max)  Weight and dimensions Net weight Netroting LAN  Veranting Security bar, Kensington Lock, Password protected interface IP5x IP5x Security bar, Kensington Lock, Password protected interface IP5x IP5x IP5x IP5x IP5x IP5x IP5x IP5x		Wiled remote, 1 x h3232
Noise level (max)  Security Security bar, Kensington Lock, Password protected interface IP rating  OSD / display languages  French, German, Greek, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese  24/7 operation  Yes  360° operation  Operating conditions  Remote control  Heat dissipation  Speaker count  Watts per speaker  10W  Networking  LAN  Yes  Power  Power consumption (min)  Power consumption (min)  Power consumption (max)  Weight and dimensions  Net weight  12.7kg  Dimensions (W x D x H)  484 x 178.5 x 376		
Security Bar, Kensington Lock, Password protected interface IP rating IP5x  OSD / display languages 23 languages: Arabic, Czech, Danish, Dutch, English, Farsi, French, German, Greek, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese  24/7 operation Yes 360° operation Yes Operating conditions 10% to 85% Humidity, non-condensing Remote control Backlit ProAV remote Heat dissipation 2.013BTU/hour Speaker count 2 Watts per speaker 10W Networking LAN Yes Power Power consumption (standby) Power consumption (min) 370W Power consumption (max) 590W Weight and dimensions Net weight 12.7kg Dimensions (W x D x H) 484 x 178.5 x 376		
IP rating  OSD / display languages  23 languages: Arabic, Czech, Danish, Dutch, English, Farsi, French, German, Greek, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese  24/7 operation  Yes  360° operation  Yes  Operating conditions  10% to 85% Humidity, non-condensing  Remote control  Heat dissipation  Speaker count  2.013BTU/hour  Speaker count  2 Watts per speaker  10W  Networking  LAN  Yes  Power  Power consumption (standby)  Power consumption (min)  370W  Power consumption (max)  590W  Weight and dimensions  Net weight  12.7kg  Dimensions (W x D x H)  484 x 178.5 x 376	, ,	
OSD / display languages  23 languages: Arabic, Czech, Danish, Dutch, English, Farsi, French, German, Greek, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese  24/7 operation  Yes  360° operation  Yes  Operating conditions  10% to 85% Humidity, non-condensing  Remote control  Backlit ProAV remote  Heat dissipation  2.013BTU/hour  Speaker count  2 Watts per speaker  10W  Networking  LAN  Yes  Power  Power consumption (standby)  Power consumption (min)  370W  Power consumption (max)  Weight and dimensions  Net weight  12.7kg  Dimensions (W x D x H)  484 x 178.5 x 376	•	
French, German, Greek, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese  24/7 operation Yes 360° operation Yes Operating conditions Remote control Heat dissipation Speaker count 2.013BTU/hour Speaker count 2 Watts per speaker 10W Networking LAN Yes Power Power Power consumption (standby) Power consumption (min) Power consumption (max) S90W Weight and dimensions Net weight 12.7kg Dimensions (W x D x H)  484 x 178.5 x 376	-	
360° operation         Yes           Operating conditions         10% to 85% Humidity, non-condensing           Remote control         Backlit ProAV remote           Heat dissipation         2.013BTU/hour           Speaker count         2           Watts per speaker         10W           Networking         LAN           LAN         Yes           Power         Power consumption (standby)           Power consumption (min)         370W           Power consumption (max)         590W           Weight and dimensions         Veright and dimensions           Net weight         12.7kg           Dimensions (W x D x H)         484 x 178.5 x 376	OSD / display languages	French, German, Greek, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish,
Operating conditions     10% to 85% Humidity, non-condensing       Remote control     Backlit ProAV remote       Heat dissipation     2.013BTU/hour       Speaker count     2       Watts per speaker     10W       Networking       LAN     Yes       Power     0.5W       Power consumption (standby)     370W       Power consumption (min)     370W       Power consumption (max)     590W       Weight and dimensions     12.7kg       Dimensions (W x D x H)     484 x 178.5 x 376	24/7 operation	Yes
Remote control         Backlit ProAV remote           Heat dissipation         2.013BTU/hour           Speaker count         2           Watts per speaker         10W           Networking         LAN           Power         Power consumption (standby)           Power consumption (min)         370W           Power consumption (max)         590W           Weight and dimensions         12.7kg           Dimensions (W x D x H)         484 x 178.5 x 376	360° operation	Yes
Heat dissipation         2.013BTU/hour           Speaker count         2           Watts per speaker         10W           Networking         LAN         Yes           Power         Power consumption (standby)         0.5W           Power consumption (min)         370W           Power consumption (max)         590W           Weight and dimensions         Net weight         12.7kg           Dimensions (W x D x H)         484 x 178.5 x 376	Operating conditions	10% to 85% Humidity, non-condensing
Speaker count         2           Watts per speaker         10W           Networking         Image: Construction of the property of the	Remote control	Backlit ProAV remote
Speaker count         2           Watts per speaker         10W           Networking         LAN         Yes           Power         Power consumption (standby)         0.5W           Power consumption (min)         370W           Power consumption (max)         590W           Weight and dimensions         12.7kg           Dimensions (W x D x H)         484 x 178.5 x 376	Heat dissipation	2.013BTU/hour
Watts per speaker         10W           Networking         Ves           LAN         Yes           Power         0.5W           (standby)         Power consumption (min)           Power consumption (max)         590W           Weight and dimensions         Very consumption (max)           Net weight         12.7kg           Dimensions (W x D x H)         484 x 178.5 x 376	Speaker count	2
Networking	•	10W
LAN         Yes           Power            Power consumption (standby)         0.5W           Power consumption (min)         370W           Power consumption (max)         590W           Weight and dimensions         12.7kg           Dimensions (W x D x H)         484 x 178.5 x 376		
Power         0.5W           Power consumption (standby)         0.5W           Power consumption (min)         370W           Power consumption (max)         590W           Weight and dimensions         12.7kg           Dimensions (W x D x H)         484 x 178.5 x 376	•	Yes
Power consumption (standby)         0.5W           Power consumption (min)         370W           Power consumption (max)         590W           Weight and dimensions         12.7kg           Dimensions (W x D x H)         484 x 178.5 x 376		
Power consumption (max)         590W           Weight and dimensions         12.7kg           Dimensions (W x D x H)         484 x 178.5 x 376	Power consumption	0.5W
Power consumption (max)         590W           Weight and dimensions         12.7kg           Dimensions (W x D x H)         484 x 178.5 x 376		370W
Weight and dimensions         12.7kg           Net weight         12.7kg           Dimensions (W x D x H)         484 x 178.5 x 376		590W
Net weight         12.7kg           Dimensions (W x D x H)         484 x 178.5 x 376		
<b>Dimensions (W x D x H)</b> 484 x 178.5 x 376		12.7kg
mm	Dimensions (W x D x H)	9



