datasheet PA503W



Key Features

HIGHER BRIGHTNESS. LONGER LAMP LIFE.

- 22,000:1 contrast ratio
- SuperColor™ technology
- 5 colour modes
- Auto power off
- Vertical keystone



Product **Description**

The ViewSonic PA503W offers impressive visual performance in small business meeting rooms and classrooms. With higher brightness and longer lamp life, PA503W projector is guaranteed to reproduce the finest of details in any environment for much longer. ViewSonic exclusive SuperColour™ technology offers a wider range of displayable colour ensuring true-to-life colour accuracy in both bright and dark environments without sacrificing image quality.





datasheet_PA503W

		datasheet_PA503W	
SPECIFICATION		OTHERS	
Native Resolution:	1280x800	Power Supply Voltage:	100-240V+/- 10%, 50/60Hz AC
DC type:	DC3	Power Consumption:	Normal: 260W
Brightness:	3600 ANSI Lumens	Fower Consumption.	Standby: <0.5W
Contrast Ratio with SuperEco mode:	22000:1	Operating Temperature:	0~40°C
Display Colour:	1.07 Billion Colours	Carton:	Brown
Light Source:	Lamp	Net Weight:	2.2kg
Light source life (Nor/SuperEco):	5000/15000	Dimensions (WxDxH) w/adjustment foot:	294x218x110mm
Lamp Watt:	200W	Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese
Lens:	F=2.56-2.68, f=22-24.1 mm		
Projection Offset:	100%+/-5%		
Throw Ratio:	1.55~1.70		
Image size:	30" - 300"		
Throw Distance:	1m-10.98m(100" @3.34m)	STANDARD ACCESSORY	
Keystone:	±40° (Vertical)	Power Cord:	1
Optical Zoom:	1.1x	VGA cable:	1
Audible Noise (Eco):	27dB	Remote Control:	1
Resolution Support:	VGA(640 x 480) to FullHD(1920 x 1080)	QSG & CD: Air Filter:	QSG: 1 / CD: NA RSPL
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p		
Video Compatibility:	NTSC, PAL, SECAM		
Horizontal Frequency:	15K~102KHz		
Vertical Scan Rate:	23~120Hz		
INPUT			
Computer in (D-SUB 15 pin):	2		
Composite:	1		
Audio-in (3.5mm):	1		
HDMI:	1 (Back)		
OUTPUT			
Monitor out (D-SUB 15 pin):	1		
Audio out (3.5mm):	1		
Speaker:	2W		
CONTROL			
RS232:	1		
USB type mini B (Services):	1		

Copyright $\ensuremath{\mathbb{C}}$ ViewSonic Corporation 2000-2020. All rights reserved.