Key **Features**

Bright Images in Any Environment | Long Lamp Life | Vertical Lens Shift | Cloud-based Color Profile Exchange | SuperColor: Amazing Color Accuracy



Product **Description**

Ideal for both home entertainment and office use, the ViewSonic® PX701HDH delivers stunning Full HD images for versatile projection. With 3,500 ANSI lumens, this high-brightness projector delivers clear pictures even in brightly lit rooms. What's more, an energy-saving SuperEco™ feature reduces power consumption and extends the lamp life by up to 20,000 hours,* effectively reducing lamp replacement and maintenance costs. A cloud-based vColorTuner™ feature allows users to customize and save color profiles, while exclusive SuperColor™ technology offers a wide color gamut for beautiful image production in nearly any environment. Dual HDMI inputs and USB power supply delivers flexible connectivity options for gaming, movies, wireless dongles, and more.



- 1. Control Panel
- 2. Elevation Foot
- 3. Zoom Ring
- 4. IR Remote Sensor
- 5. Projection Lens
- 6. USB 2.0 Type A



- 7. HDMI (x2)
- 8. Audio In/Out
- 9. AC In
- 10. RS232
- 11. Kensington® Lock Slot





LUMENS



1.5-1.65

THROW RATIO



Display:

DLP Lamp Type:

Full HD (1920x1080) Resolution Type:

Resolution: 1920 x 1080

Brightness (Lumens): 3,500 ANSI

Display Size (in.): 30 - 300 in. / 0.76 - 7.62 m Throw Distance: 1m~10.96m (100"@3.32m)

Throw Ratio: 1.5-1.65

Vertical (+/- 40°) Keystone: Lens: 1.1x optical zoom

Light Source (watt): 203 Light Source Life, Normal (hours): 5000 Light Source Life, Dynamic Eco-

20000

Mode (hours):

Color Depth: 1.07 Billion Colors

Dynamic Contrast Ratio: 12,000:1 Aspect Ratio: 16:9

Video Signal:

Frequency Horizontal: 15K-102KHz Frequency Vertical: 23-120Hz

Compatibility:

PC Resolution (max): 1920 x 1200 PC Resolution (min): 640 x 480 Mac® Resolution (max): 1920 x 1200 Mac® Resolution (min): 640 x 480

Connector:

USB 2.0 Type A(1), 3.5mm Audio Out(1), 3.5mm Audio In(1), Control (RS232)(1), HDMI 1.4 (with HDCP 1.4)(2)

Audio:

Internal Speakers: 10W (x1)

Power:

100-240V+/- 10%, 50/60Hz AC Voltage:

300W Consumption (typical): Stand-by: <0.5W

Controls:

Physical Controls: Keypad, Power key

Display, Image, Power Management, Basic, Advanced, System, On Screen Display:

Information (See user guide for full OSD functionality)

Operating Conditions:

32-95° F (0 - 35° C) Temperature:

Additional Hardware:

Kensington Lock Slot:

Weight (imperial):

Net (lbs): 5.7 Gross (lbs): 8.3

Weight (metric):

Net (kg): 2.6 Gross (kg): 3.8

Dimensions (imperial) (WxHxD):

Packaging (in.): 16.3 x 6.6 x 11.7

Physical (in.): 12.2 x 4.4 x 8.7

Dimensions (metric) (WxHxD):

Packaging (mm): 415.0 x 168.0 x 297.0 Physical (mm): 312.0 x 108.0 x 222.0

General:

Regulations: cTUVus

PACKAGE CONTENTS: PX701HDH projector, power cable, remote control, Quick Start Guide

Warranty: Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

UPC: 766907016758

Accessories:

HB10B, PJ-CASE-008, PJ-SCW-1001W, PJ-WMK-006, RLC-119, VCB10, VSR100

Copyright © ViewSonic Corporation 2000-2022. All rights reserved. (02/22/2022 01:04 PM PST)